

523 024  
10/523 024

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property  
Organization  
International Bureau



(43) International Publication Date  
12 February 2004 (12.02.2004)

PCT

(10) International Publication Number  
**WO 2004/013583 A1**

(51) International Patent Classification<sup>7</sup>: **G01F 23/24**

(21) International Application Number:  
PCT/IT2003/000451

(22) International Filing Date: 22 July 2003 (22.07.2003)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:  
RM2002A000415 2 August 2002 (02.08.2002) IT

(71) Applicant (for all designated States except US): **AXANA 2000 S.R.L.** [IT/IT]; Via Castellana, 12D, I-36060 Romano d'Ezzalino (VI) (IT).

(72) Inventors; and

(75) Inventors/Applicants (for US only): **MANFIOTTO, Arcangelo** [IT/IT]; Axana 2000 s.r.l., Via Castellana, 12D,

I-36060 Romano d'Ezzalino (VI) (IT). **SVALDI, Paolo** [IT/IT]; Axana 2000 s.r.l., Via Castellana, 12D, I-36060 Romano d'Ezzalino (VI) (IT).


(74) Agents: **IANNONE, Carlo, Luigi et al.**; Ing. Barzano' & Zanardo Roma S.P.A., Via Piemonte, 26, I-00187 Rome (IT).

(81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (regional): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE,

[Continued on next page]

(54) Title: **PROBE TO DETECT THE LEVEL OF A LIQUID PARTICULARLY WATER WITHIN A BOILER PARTICULARLY IN A SMALL ELECTRIC HOUSEHOLD APPLIANCE**



(57) Abstract: The invention relates to a probe (1) to detect the level of a liquid, particularly water, within a boiler (10), particularly in a small electric household appliance, comprising a probe plug (2), provided at the bottom with a joint (5) for coupling with the boiler body (10), a metallic disc element (7) for the electric contact, a metallic spring (6), provided on said probe plug (2), and in contact with said metallic disc (7), and the upper part of which contacts said spring, and means (11) for supplying said probe and/or transmitting the signal to an electric board, coupled with said metallic disc (7).

WO 2004/013583 A1

WO 2004/013583 A1



ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO,  
SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM,  
GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

*For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.*

**Published:**

— *with international search report*

PROBE TO DETECT THE LEVEL OF A LIQUID,  
PARTICULARLY WATER, WITHIN A BOILER,  
PARTICULARLY IN A SMALL ELECTRIC HOUSEHOLD  
APPLIANCE

5

The present invention relates to a probe to detect the level of a liquid, particularly water, within a boiler, particularly in a small electric household appliance.

10 More specifically, the invention concerns a probe of the above kind able to allow to precisely determine the level of the liquid present within the boiler.

As it is well known, different kind of vapour generators exist, to be applied on small electric household appliance. They can be roughly divided into two classes:

15

1) closed pressure boiler;

2) continuous recharge pressure boiler.

20

The first type of boiler provides a boiler element, usually comprised of stainless steel or aluminium, an inner or outer resistance, to heat the liquid (water), a pressure switch for measuring the pressure within the boiler and connected with the resistance power supply or at the moment of the measure of the wished pressure disconnects the supply to the current, and other safety components such as thermostats and safety cap, and finally systems to determine the exhaustion of the water within the boiler, such as a bulb thermostat.

25

As to the continuous recharge pressure boiler, giving the best performances, provide a boiler, usually comprised of stainless steel or aluminium, an inner or outer resistance, to heat the liquid (water), a pressure switch for measuring the pressure within the boiler and connected with the resistance power supply, other safety components such as thermostats and safety valve, and finally a system to determine the level of the water into the boiler by a probe controlled by an electronic board. Discharge of water coming from a cold water reservoir occurs thanks to a pump operated when the probe detects that the water level within the boiler is lowered.

35

Furthermore, other continuous recharge systems exist giving not satisfying results in terms of vapour quality.

At present, control of water level in a boiler is based on the principle of the ionic conductivity of water: probe, supplied at low tension, when laps the water, causes the passage of a little current, that is perceived and processed by the electronic board.

5           The probe, insulated by a Teflon<sup>®</sup> joint with respect to all the others components that can be in contact with the boiler, must be fed by an electronic board.

10           Connection for the signal transmission between the probe and the board usually is realised by a direct outer contact through an electric wire.

15           This kind of solution is characterised by the drawback that an outer wire is always present, which is subjected to wearing. Furthermore, it can be accidentally disconnected since placed outside, and thus the connection can be lost. To solve this drawback, it can be hidden in a suitable seat protected by a cover.

20           It is further possible that, being it necessary to intervene for routine maintenance reasons, it is necessary to remove the probe and when it is put again in its original position, the operator forgets to connect it with the wire or insert it in a wrong way, thus causing the malfunction of the system.

          In order to overcome these drawbacks, it is suggested the solution according to the present invention, providing a probe connected with the electronic board by an indirect coupling.

25           It is therefore specific object of the present invention a probe to detect the level of a liquid, particularly water, within a boiler, particularly in a small electric household, comprising a probe plug, provided at the bottom with a joint for coupling with the boiler body, a metallic disc element for the electric contact, a metallic spring, provided on said probe plug, and in contact with said metallic disc,  
30           and the upper part of which contacts said spring, and means for supplying said probe and/or transmitting the signal to an electric board, coupled with said metallic disc.

          Preferably, according to the invention, said joint is comprised of Teflon<sup>®</sup>.

35           Still according to the invention, said metallic disc is coupled with the probe plug by screws or rivets, or by overprinting.

Always according to the invention, said spring is a substantially U- shaped spring. Straddled on the probe plug, possibly housed in a suitable seat, and having foot contacting said metallic disc.

5 Furthermore, according to the invention, it is provided a metallic contact, preferably a spring, exiting from the housing of the boiler and contacting with said metallic disc.

10 The present invention will be now described, for illustrative but not limitative purposes, according to its preferred embodiments, with particular reference to the figures of the enclosed drawings, wherein:

figure 1 is a perspective exploded view of a probe according to the invention;

figure 2 is an exploded front view of the probe of figure 1;

15 figure 3 is a perspective view of the plug of the probe according to the invention;

figure 3a shows a particular of the plug of figure 3;

figure 3 is a top view of the plug of the figure 3;

figure 5 is a perspective rear view of the plug of figure 3;

20 and

figure 6 schematically shows a boiler provided with a probe according to the invention.

25 Observing first figures 1 – 5 of the enclosed drawings, it is shown a probe according to the invention, generically indicated by the reference number 1, providing a plug probe 2, a probe body 3, a probe 4, a Teflon® joint 5, a spring 6, a conductive disc 7, and screws or rivets 8 for anchoring to the conductive tube 9 (that can be seen in figure 6).

30 Usually, as it can be noted from figure 6, a continuous recharge vapour generator is usually comprised of a boiler 10, a resistance for heating water, a pump for supplying water into the boiler 10, a probe 4 aiming to read the water level present within the boiler 10, an electronic board (not shown) processing the data provided by the probe 4 and controlling the phases of the vapour generation process.

35 In the solution suggested according to the present invention, connection between the probe 4 and the board occurs by an indirect

contact, so that a conductive object 11 is supplied, that supplies the probe 4.

5           The probe according to the present invention is supplied by the steel disc 7 anchored to the insulating plug 2 of the probe 1, that is contacted with a spring 6 lapping the end of the probe 1.

          The system operates properly if, during the operation of the boiler 10, the passage of a clear signal is guaranteed through the probe 4, without noise signals that could jeopardise the proper operation of the system.

10           The above result is obtained if good contacts between the conductive parts of the probe are ensured.

          By the solution according to the present invention a good contact is obtained by the fact that the disc 7, lapping the "foot" of the spring 6 is tightened on the probe plug 2 by the rivets 8, and by  
15           the fact that the end of the probe is fixed to the spring. Contact is further ensured when the probe 4 is inserted in the proper seat of the boiler 10.

          In fact, when it is screwed, it exerts a further pressure on the disc 7, and consequently on the spring 6 – disc 7 contact.

20           By this solution, the user can unscrew the probe plug 2 as wished without the preoccupation of acting on the probe 4 to disactivate/activate the electric contact.

          To prevent that turbulences of the vapour within the boiler 10 do not create noise signals (false signals), a Teflon® joint 3 close to  
25           the probe plug 2, where, due to the water film, electric jumpers could be formed between the part under tension of the probe 1 and the part in contact with the ground boiler 10.

          The present invention has been described for illustrative but not limitative purposes, according to its preferred embodiments, but it  
30           is to be understood that modifications and/or changes can be introduced by those skilled in the art without departing from the relevant scope as defined in the enclosed claims.

5  
CLAIMS

1. Probe to detect the level of a liquid, particularly water, within a boiler, particularly in a small electric household appliance, characterised in that it comprises a probe plug, provided at the bottom with a joint for coupling with the boiler body, a metallic disc element for the electric contact, a metallic spring, provided on said probe plug, and in contact with said metallic disc, and the upper part of which contacts said spring, and means for supplying said probe and/or transmitting the signal to an electric board, coupled with said metallic disc.

2. Probe according to claim 1, characterised in that said joint is comprised of Teflon®.

3. Probe according to one of the preceding claims, characterised in that said metallic disc is coupled with the probe plug by screws or rivets, or by overprinting.

4. Probe according to one of the preceding claims, characterised in that said spring is a substantially U- shaped spring. Straddled on the probe plug, possibly housed in a suitable seat, and having foot contacting said metallic disc.

5. Probe according to one of the preceding claims, characterised in that it is provided a metallic contact, preferably a spring, exiting from the housing of the boiler and contacting with said metallic disc.

6. Probe to detect the level of a liquid, particularly water, within a boiler, particularly in a small electric household appliance, according to each one of the preceding claims, substantially as illustrated and described.




Fig. 1




Fig. 2



2/2




Fig. 3




Fig. 4




Fig. 5




Fig. 6

# INTERNATIONAL SEARCH REPORT

International Application No  
PCT/IT 03/00451

## A. CLASSIFICATION OF SUBJECT MATTER

IPC 7 G01F23/24

According to International Patent Classification (IPC) or to both national classification and IPC

## B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 G01F

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

EPO-Internal, PAJ, WPI Data

## C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	US 2002/053240 A1 (AMORETTI LUIGI) 9 May 2002 (2002-05-09) abstract; figure 1	1
A	US 5 669 263 A (POLITT JOACHIM-CHRISTIAN DR ET AL) 23 September 1997 (1997-09-23) abstract; figures 1-4	1
A	US 4 027 534 A (ZIMMERMANN HEINO) 7 June 1977 (1977-06-07) abstract; figure 1	1

☐ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

### \* Special categories of cited documents :

- \*A\* document defining the general state of the art which is not considered to be of particular relevance
- \*E\* earlier document but published on or after the international filing date
- \*L\* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- \*O\* document referring to an oral disclosure, use, exhibition or other means
- \*P\* document published prior to the international filing date but later than the priority date claimed

- \*T\* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- \*X\* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- \*Y\* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.
- \*G\* document member of the same patent family

Date of the actual completion of the international search

14 November 2003

Date of mailing of the international search report

27/11/2003

Name and mailing address of the ISA  
European Patent Office, P.B. 5818 Patentlaan 2  
NL - 2280 HV Rijswijk  
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,  
Fax: (+31-70) 340-3016

Authorized officer

Vorropoulos, G

# INTERNATIONAL SEARCH REPORT

International Application No

PCT/IT 03/00451

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
US 2002053240 A1	09-05-2002	IT PD20000287 A1 EP 1217341 A2	21-06-2002 26-06-2002
US 5669263 A	23-09-1997	DE 19507616 A1 AT 228645 T CZ 9600575 A3 EP 0731343 A2 FI 960946 A NO 960282 A PL 313023 A1 ZA 9601671 A	05-09-1996 15-12-2002 11-09-1996 11-09-1996 05-09-1996 05-09-1996 16-09-1996 05-09-1996
US 4027534 A	07-06-1977	NONE	